



 $Sony^{(e)}$ chipset gives the most vibrant colour and the clearest image. It is most suitable for the happy environment of your nursery. And this lightweight, discreet dome camera gives an elegant, non-intrusive presentation.



Key Features:

- 1/3" Sony[®] Super HAD Color CCD II
- Day & Night (0.01Lux)
- Digital Wide Dynamic Range (D-WDR)
- 600 TV Lines High Resolution
 Digital Noise Reduction (2D DNR)
- Digital Noise Reduction (2D DNR)

Specifications:

Image Sensor	1/3" Sony [®] Super HAD CCD II
Horizontal Resolution	More than 600 TV Lines
Lens	3.6mm (Optional 2.9mm / 6.0mm)
Min Illumination	0.1 Lux@ F1.2 (Normal Color Mode, 50 IRE)
Effective Pixels	768(H) x 494(V) – NTSC; 752(H) x 582(V) – PAL
Video Output	CVBS : 1.0Vp-p / 75 Ohm
Scanning System	2:1 Interlace
Sync. System	Internal
Electronic Shutter Speed	1/60~1/100,000 Sec – NTSC; 1/50~1/100,000 Sec – PAL Auto / Manual / Flickerless
S/N Ratio	52dB (AGC Off, Weight On)
Operating Temp.	-14~122°F / -10~+50°C
Operating Humidity	30% ~ 80% RH
Power Supply	DC 12V / 150mA
Dimension (Φ x H)	112mm x 87mm

* Specifications are subject to change without notice



web: www.nurserycam.co.uk





The vandal-resistant housing offers better protection to the camera, while its elegant dome design makes it ideal for a less intrusive presentation, especially for listed buildings.



Outdoor VR Dome Camera

Key Features:

- 1/3" Sony[®] Super HAD CCD II
- 600 TV Lines High Resolution
- Smart IR function Auto IR intensity adjustment of objects at short distances
- Digital Noise Reduction (2D DNR)
- 24 IR LED for Low light Environment

Specifications:

Image Sensor	1/3" Sony [®] Super HAD CCD II
Horizontal Resolution	More than 600 TV Lines
Lens	3.6mm (Optional 2.9mm / 6.0mm)
Min Illumination	0.01 ux@ F1.2 (Normal Color Mode, 50 IRE0 0.000 Lux (CDS On)
Effective Pixels	768(H) x 494(V) – NTSC; 752(H) x 582(V) – PAL
Video Output	CVBS: 1.0Vp-p / 75 Ohm
Scanning System	2:1 Interlace
Sync. System	Internal
Electronic Shutter Speed	1/60~1/100,000 Sec – NTSC; 1/50~1/100,000 Sec – PAL Auto / Manual / Flickerless
S/N Ratio	52dB (AGC Off, Weight On)
Operating Temp.	14°F~122°F / -10~+50°C
Operating Humidity	30% ~ 85% RH
Power Supply	DC 12V / 300mA
Dimension (Φ x H)	97mm x 80mm
* Specifications are subject to change without notice	

* Specifications are subject to change without notice



web: www.nurserycam.co.uk